

4GS

SUBMERSIBLE PUMPS



Performance Table(n=2900r/min)

Model	Power		Volt	Flow	Head	Pump dia.	Package Dimensions & GW				
	HP	kW	V	m ³ /h	m	inch	L	W	H	Kg	
4GS2-48/8-0.55	0.75	0.55	220/380	2	48	1.25"	736	130	130	12.9	
4GS2-70/12-0.75	1	0.75			70		859			15.1	
4GS2-96/16-1.1	1.5	1.1			96		1027			18.3	
4GS2-120/20-1.5	2	1.5			120		1205			22.1	
4GS2-156/26-2.2	3	2.2			156		1462			27.5	
4GS2-210/35-3	4	3			380		210			1627	37.3
4GS2-282/47-4	5.5	4	282	2244		42.6					
4GS3-39/7-0.75	1	0.75	220/380	3	39	1.5"	713	130	130	14.2	
4GS3-55/10-1.1	1.5	1.1			55		851			17.2	
4GS3-77/14-1.5	2	1.5			77		1029			21.1	
4GS3-110/20-2.2	3	2.2			110		1285			26.5	
4GS3-148/26-3	4	3	380	5	148	1.5"	1590	130	130	36.8	
4GS3-198/36-4	5.5	4			198		1918			42.8	
4GS3-264/48-5.5	7.5	5.5			264		2362			50.9	
4GS5-30/6-0.75	1.1	0.75			220/380		5			30	708
4GS5-45/9-1.1	1.5	1.1	45	855		17.2					
4GS5-60/12-1.5	2	1.5	60	1012		20.9					
4GS5-80/16-2.2	3	2.2	80	1220		25.9					
4GS5-115/23-3	4	3	380	115		1554		35.5			
4GS5-150/30-4	5.5	4		150		1813		40.8			
4GS5-195/39-5.5	7.5	5.5		195	2191	47.5					
4GS5-265/53-7.5	10	7.5	220/380	8	265	2"	2699	130	130	54.1	
4GS8-27/5-1.5	2	1.5			27		890			19.6	
4GS8-38/7-2.2	3	2.2			38		1074			24.2	
4GS8-54/10-3	4	3			380		54			1329	33.4
4GS8-76/14-4	5.5	4					76			1657	38.4
4GS8-103/19-5.5	7.5	5.5					103			2005	44.6
4GS8-140/26-7.5	10	7.5	140	2427		49.4					