

Performance Table(n=2900r/min)

Model	Power		Volt	Flow	Head	Pump dia.	Package Dimensions & GW			
	HP	KW	V	m ³ /h	m	inch	L	W	H	Kg
6SR5-32/4-0.75	1	0.75	220/380	5	32	2"	650	230	170	25
6SR5-40/5-1.1	1.5	1.1			40		720			26.5
6SR5-56/7-1.5	2	1.5			56		920			32.5
6SR5-80/10-2.2	3	2.2			80		960			38
6SR5-114/14-3	4	3	380		114				55	
6SR8-32/4-1.1	1.5	1.1	220/380	8	32		760			25
6SR8-40/5-1.5	2	1.5			40		880			33
6SR8-56/7-2.2	3	2.2			56		970			37
6SR8-80/10-3	4	3			80		1010			41
6SR10-50/7-2.2	3	2.2	380	10	50		1220			54
6SR10-64/9-3	4	3			64		1260			58
6SR10-85/12-4	5.5	4			85		1440			67
6SR10-113/16-5.5	7.5	5.5			113		1660			76.5
6SR10-156/22-7.5	10	7.5			156		1910			98
6SR16-32/4-2.2	3	2.2	380	16	32	2.5"	1120	230	190	50
6SR16-41/5-3	4	3			41		1160			55
6SR16-57/7-4	5.5	4			57		1260			58
6SR16-73/9-5.5	7.5	5.5			73		1560			73
6SR16-98/12-7.5	10	7.5			98		1710			95
6SR25-30/3-3	4	3	380	25	30		1040			55
6SR25-40/4-4	5.5	4			40		1160			60
6SR25-50/5-5.5	7.5	5.5			50		1260			64
6SR25-70/7-7.5	10	7.5			70		1390			79

